



Short Term Noise Monitoring Program, Brookfield

28 July 2023 - 21 October 2023

Version Control

Version	Date	Comments	Sections
1.0	10 April 2024	Initial Version	All

Summary

Deployment Purpose

This deployment aims to capture noise levels of arrival and departure operations south of the airport in the Brookfield area.

Deployment monitoring Period

28 July 2023- 21 October 2023

Monitoring Details

Capture zone: 2.5km radius x 13,123ft (4,000m) altitude.

Threshold settings: 00:00-05:59 = Threshold 40dB(A), 06:00-09:59 = Threshold 51dB(A), 10:00-17:59 = Threshold 49dB(A), 18:00-23:59 = Threshold 43dB(A)

Key Findings

Noise Correlation

The purpose was to determine the number of aircraft correlated noise events (CNEs) captured by the noise monitor during the three-month deployment. 71.5% of the aircraft from Brisbane airport, as per the focus group, generated noise events that correlated to the aircraft.

Noise Daily Distribution

The purpose was to establish the number of aircraft where the maximum noise level (LaMax) of the noise event created by the aircraft exceeded a specific threshold. 79% of the maximum noise level generated by aircraft fall within the range of 55dB(A) to 65dB(A).

Most Common aircraft

The purpose was to identify the most prevalent aircraft during the deployment period, which was the B738 aircraft.

• Top loudest noise events

The purpose was to verify the accuracy of the top 100 loudest (LaMax) noise events. The top 10 noise events for this deployment originated from community sources. Additionally, the top 10 correlated noise events were associated with community sources in addition to aircraft noise.

Busiest Day

The purpose was to analyze the day that had the most significant impact on the community. The busiest day during the deployment period occurred on 3 August 2023.

Short Term Noise Monitoring – Brookfield, October 2023

Glossary of Terms

A	Arrivals
Background noise Level (L90)	The noise level in dB(A) that is exceeded 90% of the time. It is considered the background noise level of an environment.
Capture Zone	The region relative to the noise monitor that an aircraft can be within and be able to be correlated to a noise event.
Correlated Noise Event (CNE)	A noise event matched to an aircraft movement that flew through the capture zone.
D	Departures
Data Availability	The degree of data completeness achieved during the deployment period. The data availability percentage factors in any monitor outages that occur.
Day	6:00am-10:00pm
dB(A)	A-weighted decibel. It is an expression of the relative loudness of sounds as perceived by the human ear.
General Aviation	Movements other than scheduled commercial airline operations. This includes private, sports, charter and training operations.
LaMax	Each noise event will have a peak noise level which is referred to as the maximum sound level in dB(A) or LaMax
Local	Movement that departs and arrives at the same airport, including circuits and training flights.
Movement	An aircraft operation, such as an arrival or departure
Night	10:00 pm to 6:00 am
NMT	Noise Monitoring Terminal also referred to as the noise monitor.
Noise Event	A noise event is created when the noise level exceeds the threshold settings for a specified period.
0	Overflight i.e. an aircraft movement that flew over the area but did not arrive or depart from the airport of concern.
Overall Correlation Percentage	The total number of correlated noise events (CNE) is divided by the total number of aircraft movements through the capture zone to calculate the overall correlation percentage.
RWY	Runway
т	An operation by an aircraft that arrives and departs on a runway without stopping or exiting the runway. It is also known as Touch and Go.
Threshold	The threshold represents the value that the noise level must surpass for a specified period to create a noise event.
YBBN	Brisbane Airport, Queensland

Short Term Noise Monitoring – Brookfield, October 2023

Table of Contents

Sho	rt Term	Noise Monitoring Program, Brookfield	1
Vers	sion Co	ontrol	2
Sum	nmary		2
Glos	ssary of	f Terms	3
1 Ρι	urpose .		5
2 De	eployme	ent Details	6
3 Fi	ndings.		6
3.1.	Noise C	Correlation Summary	6
3.2.	Daily Di	istribution of Correlated Noise Events	8
3.3.	Most Co	ommon Aircraft	11
3.4.	Top 10 (Correlated Aircraft	11
3.5.	Noise E	Event Analysis	12
4 Bı	usiest D	Day Analysis	15
4.1.	Discuss	sion	15
4.2.	Busiest	Day Graph	16
4.3.	Busiest	Day Noise Levels	17
5 Fι	urther In	nformation	17
5.1.	Airservio	ices Australia	17
5.2.	Aircraft i	in Your Neighbourhood	17
5.3.	WebTra	ak	17
5.4.	Brisbane	ne Airport	17
6 A	opendix	κ	18
6.1.	Noise E	Event Detection Details:	18
	6.1.1.	Threshold Settings	18
	6.1.2.	Aircraft and Noise Event Correlation	18
6.2.	Calibrati	tion Check	19

1 Purpose

The short-term noise monitoring program target's locations in suburbs chosen by Airservices Australia with consideration for community feedback. This deployment aims to capture noise levels of arrival and departure operations south of the airport in the Brookfield area. Furthermore, we will conduct an extensive analysis on a selected day, specifically the busiest day of the deployment period. This day has been chosen due to its potential to offer significant statistical data and insight into a day that has the greatest impact on the community during the deployment. The analysis will provide details of the loudest noise events experienced and the most prevalent aircraft operations observed.

To adequately depict the variation in flight paths, weather conditions and operational patterns from Brisbane airport movements, a monitoring period between 28 July 2023–21 October 2023 was deemed sufficient.

This short-term monitor was deployed in Brookfield, QLD. The noise monitoring terminal (NMT) was positioned to capture aircraft within a three-dimensional cylinder capture zone. The zone spans a radius of 2.5km and extends to 13,123ft (4,000m) above the NMT site level as depicted in Figure 1. Considering that the focus group of aircraft operate below 12,000ft (3,657m), a ceiling of 13,123ft (4,000m) was adopted to accommodate potential variations.

The Focus Group for this deployment consists of aircraft operating to the south Brisbane airport which include:

- Fixed-wing aircraft arriving at runway 01L and 01R of YBBN.
- Fixed-wing aircraft departing from runway 19R and 19L of YBBN.
- All touch-and-go and helicopter YBBN operations flying into the correlation zone.



Figure 1: NMT Correlation Zone of 2.5km radius x 13,123ft altitude zone of the monitor

OFFICIAL

The focus group excludes fixed-wing aircraft departures from runway 01R and 01L, as these few turboprops aircraft that do fly over the monitor are travelling over 13,000ft. These aircraft are unable to generate a noise level significant enough to be detected by the noise monitor and trigger a noise event.

2 Deployment Details

The Brookfield monitor was installed on 27 July 2023 and removed on 22 October 2023. Complete data is available from 28 July 2023 to 21 October 2023.

NMT ID	392			
Deployment Period	28/07/2023 - 21/10/2023			
Location	Jones Road Brookfield, QLD 4069			
NMT Altitude	200ft (61m)			
Capture Zone	2.5km radius x 13,123ft (4,000m) altitude			
Data Availability	99.9%			
Threshold Settings ¹	The noise detection thresholds which have been selected: • 00:00-05:59 = Threshold 40dB(A) • 06:00-09:59 = Threshold 51dB(A) • 10:00-17:59 = Threshold 49dB(A) • 18:00-23:59 = Threshold 43dB(A)			

Table 1: NMT Details



3.1. Noise Correlation Summary

The total number of aircraft correlated noise events (CNEs) that were captured by the noise monitor during the three-month deployment period is shown in Table 2 below.

	All Movements ²	Brisbane Airport Movements	Brisbane Airport Focus Group	
Number of Movements through capture zone	6378	4765	4737	
Number of CNE	4270	3393	3388	
Correlation Summary	66.9%	71.2%	71.5%	

 Table 2: Aircraft correlation rate

¹ Threshold setting procedures are explained in section 6.1.1.

² All-movement tab accounts for operations to and from other airports (E.g. Amberley, Archerfield and Wellcamp) as well as YBBN operations.

74.7% of all operations that passed through the capture zone were Brisbane airport movements. A one-week sample of these movements is shown in Figure 2, below. Other operations included traffic from other airports, such as Amberley, Archerfield, and Wellcamp Airports.

A correlation of 71.5% was achieved for the focus group of Brisbane airport movements. The uncorrelated jet and turboprop aircraft from the focus group failed to correlate due to their higher altitude of 8000 to14,000ft when passing over the noise monitor, hence were unable to produce a noise level above the threshold.



Figure 2: One week of Brisbane airport flight tracks passing through the correlation zone

The findings obtained during the short-term deployment at Brookfield are as follows:

- Departure runway 19R and 19L accounted for 63% and 10% of the operations respectively from Brisbane airport over the noise monitor.
- Arrival runway 01L and 01R account for 18% and 7% of the operations respectively from Brisbane airport over the noise monitor.
- The average LaMax and highest LaMax for arrival and departure runways are detailed in Table 3, below.

Short Term Noise Monitoring – Brookfield, October 2023

Operation Type	Runway	Average LaMax noise dB(A)	Highest LaMax dB(A)
Brisbane Airport Departure	19R	62.6	81.0
Brisbane Airport Arrival	01L	59.8	77.3
Brisbane Airport Departure	19L	63.6	72.4
Brisbane Airport Arrival	01R	61.5	84.4

Table 3: Average LaMax and highest LaMax noise levels corresponding to each runway.

3.2. Daily Distribution of Correlated Noise Events

A summary of the total number of correlated noise events by time of day, and the minimum to maximum number of CNE on any day, are summarized below in Table 4.

Correlated Noise Event (CNE)	Day Time Count (6:00am- 10:00pm)	Night-time Count (10:00pm- 6:00am)	Min number of CNE per day	Max number of CNE per day
N- Above ³ 50 dB(A) (N50+ ⁴)	2894	506	9	82
N- Above 60 dB(A) (N60+ ⁴)	1445	208	1	56
N- Above 70 dB(A) (N70+ ⁴)	50	2	0	4

Table 4: Total correlated noise events during deployment period by time

Examination of the N-above distribution values in Figure 3 and Figure 4 (below) show that the highest daytime noise levels (N70+) were recorded on 14 September, and nighttime distribution peaks were observed on 3 August and 23 September. 79% of the maximum noise level generated by aircraft falls within a range of 55dB(A) to 65dB(A), with only 1.4% exceeding 70dB(A).

³ N-above (or Number-above) is defined as the number of noise event with a LaMax above the specified (eg.N50+) value.

 $^{^{4}}$ N50+, N60+, N70+ are expressed as number of noise events with a LaMax above 50dB(A), 60 dB(A) and 70 dB(A), respectively.

Short Term Noise Monitoring – Brookfield, October 2023



Figure 3: Daytime Daily N-Above Distribution Graph

Short Term Noise Monitoring – Brookfield, October 2023



Figure 4: Night-time Daily N-Above Distribution Graph

3.3. Most Common Aircraft

The most common aircraft type that flew through the zone during the deployment period is a B738 aircraft as shown in Table 5, below.

Brisbane Airport Operation Type	Operations	Correlated %
Arrival	66	80%
Departure	1010	75%
Touch and Go	1	100%
Overflight	1	100%

Table 5: B738 correlation percentage across the deployment period

3.4. Top 10 Correlated Aircraft

The following table shows the top 10 average and maximum noise levels of correlated noise events (CNEs) for the deployment period from 28 July to 21 October. The highest average LaMax of 63dB(A) is attributed to B738 jet aircraft departing from runway 19R, shown in Table 6.

Aircraft Type	Aircraft Category	Airport Code	Operation Type	Runway	Total CNE	Average LaMax dB(A)	Max dB(A)
B738	J	YBBN	D	19R	696	63.0	81.0
F100	J	YBBN	D	19R	297	62.8	74.5
E190	J	YBBN	D	19R	296	61.9	71.3
F70	J	YBBN	D	19R	267	61.6	73.7
A320	J	YBBN	D	19R	253	59.6	69.8
DH8D	Т	YBBN	A	01L	226	59.3	77.3
B737	J	YBBN	D	19R	84	62.4	74.2
B738	J	YBBN	D	19L	71	61.7	67.7
B77W	J	YBBN	D	19L	71	67.0	70.6
A359	J	YBBN	D	19R	65	61.2	65.3

 Table 6: Top 10 aircraft in the deployment period by total CNE

Aircraft Type: J = Jets, T = Turboprop. Operation Type: D = Departure, A = Arrival

3.5. Noise Event Analysis

The audio verification process involved listening to and confirming the accuracy of the top 100 loudest (LaMax) noise events.

Table 7 outlines the top 10 noise events from all sources. The maximum noise levels (LaMax) of the noise events for this deployment were all from community sources such as birds, strong winds or rain, and machinery.

Table 8 outlines the top 10 correlated noise events (that is, aircraft noise). The maximum noise levels (LaMax) of correlated noise events for this deployment originated from other nearby local airport movements as well as Brisbane Airport movements.

Some correlated noise events were associated with community sources in addition to aircraft. This can be seen in the 'noise source' details in Table 8 and Figure 5. Consequently, there may be a benefit in conducting further noise monitoring in this location to explore and confirm the spectrum of noise levels attributed to aircraft, with the exclusion of any impact from community noise contamination.

Future aircraft noise monitoring in the Brookfield area can achieve more precision by:

- Choosing a location with fewer trees will minimise the contamination of the noise events by wildlife.
- Selecting autumn and winter periods, typically between May and August, for deployment. During these seasons, bird activity tends to decrease, thereby reducing the amount of bird noise captured in the noise events.

Start Date/Time	Correlated to Aircraft?	LaMax dB(A)	Noise Source	Aircraft Type	Operation Type	Runway
08/09/2023 14:24	No	107.7	Alarm	-	-	-
18/09/2023 15:32	No	92.8	Birds	-	-	-
27/08/2023 16:09	No	91.4	Birds	-	-	-
07/09/2023 16:20	No	88.7	Birds	-	-	-
05/09/2023 16:41	No	88.5	Birds	-	-	-
06/08/2023 15:22	No	88.2	Birds	-	-	-
09/09/2023 15:24	No	87.4	Birds	-	-	-
28/09/2023 15:01	No	86.9	Thunder	-	-	-
24/08/2023 11:58	No	86.0	Birds	-	-	-
12/10/2023 17:41	No	86.0	Lawn Mower	-	-	-

Table 7: Top 10 loudest noise events during the deployment period by LaMax

Start Date/Time	Movement Airport ⁵	LaMax dB(A)	Noise Source	Aircraft Type ⁶	Operation Type ⁷	Runway
26/08/2023 16:06	Brisbane	84.4	Aircraft and Birds	DH8D	A	01R
21/08/2023 10:40	Brisbane	81.0	Aircraft and Machinery	B738	D	19R
29/07/2023 16:58	Overflight	78.6	Aircraft and Birds	A139	0	-
27/09/2023 09:08	Overflight	78.0	Aircraft and Birds	C72R	0	-
14/09/2023 12:32	Overflight	77.6	Aircraft and Machinery	RV14	0	-
21/08/2023 10:54	Brisbane	77.5	Aircraft and Machinery	A332	D	19R
27/09/2023 16:57	Brisbane	77.3	Aircraft and Birds	DH8D	А	01L
06/10/2023 15:40	Overflight	76.3	Aircraft	-	0	-
03/08/2023 06:30	Brisbane	75.8	Aircraft and Vehicle	B738	D	19R
09/08/2023 10:32	Overflight	75.6	Aircraft and Birds	B105	0	-

Table 8: Top 10 loudest aircraft correlated noise events during the deployment period by LaMax

 ⁵ Overflights refers to movements from Amberly airport, Archerfield airport, Toowoomba airport, etc.
 ⁶ Dash (-) indicates unknown aircraft types
 ⁷ Operation types A = Arrival, D = Departure, O = Overflight, T = Touch and Go



Short Term Noise Monitoring – Brookfield, October 2023

Brisbane International Airport

Single Noise Event

21/08/2023 10:40:02 AM-21/08/2023 10:40:53 AM

Machinery

10:40:10 AM 10:40:20 AM 10:40:30 AM 10:40:40 AM 10:40:50 AM

Time (Local Time)

- Loc 392



Max Date/Time 21/08/2023 10:40:24 AM

80

면 75 70

2 65

60

55

45

50 -

Flight Details

Tail Number

Beacon Code

Aircraft Type 8738

Runway Name 19R

A/D Flag

Destination

Way Point

Actual Time

Flight No

Origin

Flight Number V0Z045

VHYIT

1075

D

YBBN

WADD

21/08/202

21/08/202

V0Z045

LaMax: 81.0 dB(A)

Aircraft Noise

Max Date/Time 29/07/2023 4:58:18 PM LaMax: 78.6 dB(A)



Max Date/Time 27/09/2023 9:08:57

LaMax: 78.0 dB(A)



Max Date/Time 27/09/2023 4:57:10 PM

LaMax: 77.3 dB(A)



Figure 5: Top 9 correlated noise event from Table 8 graphed and analysed.

Max Date/Time 14/09/2023 12:32:56 PM LaMax: 77.6 dB(A)



Max Date/Time 6/10/2023 3:41:16 PM LaMax: 76.3 dB(A)



Max Date/Time 21/08/2023 10:54:40 AM LaMax: 77.5 dB(A)





Page 14

4 Busiest Day Analysis

4.1. Discussion

The busiest day during the deployment period occurred on 3 August, with a total of 199 noise events. The noise events consisted of jet, helicopter, turboprop, bird, machinery, and vehicle noise. There were 95 aircraft captured passing through the zone from Brisbane airport movements, all of which were from the focus group. The predominant movement over the capture zone was from jet operations (98%).



Figure 6: Busiest day flight tracks

4.2. Busiest Day Graph



Figure 7: Distributions of max CNE level, hourly L90 and one-second noise data on the busiest day

4.3. Busiest Day Noise Levels

The loudest event on the busiest day was created by birds, reaching a maximum noise level of 77.5 dB(A) at 17:46:32 in the afternoon, lasting for 10 seconds.

The loudest Brisbane airport movement on the busiest day was created during the departure of a B738 Jet from runway 19R at 06:30:27, registering a maximum noise level of 75.8 dB(A).

5 Further Information

The following platforms provide further information on Brisbane aircraft noise monitoring.

5.1. Airservices Australia

Information on the noise and flight path monitoring system including approach to noise monitoring and frequently asked questions:

https://www.airservicesaustralia.com/community/environment/aircraft-noise/monitoring-aircraftnoise/

5.2. Aircraft in Your Neighbourhood

Brisbane Noise Monitoring Report (interactive tool to explore monthly noise monitoring data): https://aircraftnoise.airservicesaustralia.com/2020/10/29/brisbane-noise-monitoring-report/

The Brisbane Noise and Flight Path Monitoring System (long term noise monitor terminal locations):<u>https://aircraftnoise.airservicesaustralia.com/2020/06/03/the-brisbane-noise-and-flight-path-monitoring-system-nfpms/</u>

5.3. WebTrak

Aircraft noise data is displayed from live noise monitors across Brisbane, along with historical data: <u>https://webtrak.emsbk.com/bne3</u>

5.4. Brisbane Airport

Dashboard for live noise monitor and PDF reports from past monitor locations provided by Brisbane Airport Corporation (all short term monitor placements): <u>https://www.bne.com.au/corporate/community-and-environment/flight-paths-aircraft-noise/noise-management</u>

6 Appendix

6.1. Noise Event Detection Details:

ISO 20906 provided technical guidance in this short-term noise monitoring. The NMT (i.e., sound level monitor) used for testing passed the Class 1 periodic calibration tests outlined in clauses of IEC 61672-3:2013 and IEC 61260-3:2016. The placement of NMT considered the vicinity of reflective surfaces and the height of the NMT relative to the target aircraft operations to minimise potential unintended anomalies. The NMT height is fixed on a supporting pole and the captured noise events were observed acceptable throughout the deployment. The background noise levels were taken into account in the monitoring area, to appropriately capture aircraft noise levels.

6.1.1. Threshold Settings

Noise monitor threshold settings are established by collecting hourly average L90 data over a period of two to five days following installation of the noise monitor. L90 represents noise level which are exceeded 90% of the time. It is considered the background noise level of an environment. For instance, if the L90 hourly noise level reads 50dB(A), it means that for 90% of that hour, the noise level is above 50dB(A). The threshold is set close to the average L90+10dB(A). The addition of 10dB(A) effectively filters out most community noise, such as birds and animal sounds, machinery, and vehicle noises. As a result, the created noise event will predominantly contain aircraft noise with minimal community noise.

6.1.2. Aircraft and Noise Event Correlation

The correlation of a noise event with an aircraft requires meeting the following conditions:

- The aircraft passes through the defined capture zone set by the monitor as shown in Figure 1.
- The rise and fall time of the measured event matches a sound pattern representative of an aircraft flyover.
- Noise levels are greater than the specified threshold for a specified period when aircraft flies over, this creates a noise event.
- Maximum noise level of the noise event known as LaMax must occur while the aircraft is within the capture zone of the noise monitor.

Aircraft that flew within the vicinity of the monitor but did not trigger a correlated noise event may have failed to meet some of the parameters above. In other instances, this could be attributed to the lack of air traffic control data (ATC). This occurs when aircraft do not have an operating transponder or when there are radar outages. Despite a noise event being created by the aircraft, without available ATC data, there will be no aircraft to correlate with the noise event.

Short Term Noise Monitoring – Brookfield, October 2023

6.2. Calibration Check

The integrity of the noise monitor relies on regularly verifying the accuracy of the microphone recording levels and time synchronisation of samples with radar data. The microphones are replaced with laboratory certified microphones every 12 months and electrostatic calibration tests are automatically performed daily to ensure data quality.